

Supplemental Amendment
Application No. 10/089,781
Attorney's Docket No. 025265-232
Page 2

AMENDMENTS TO THE SPECIFICATION

Please replace the first paragraph on page 13, starting on line 16, with the following paragraph:

Figures 8 a-and-b illustrates RMS power error contour plots ray traced for distance objects (object distance of infinity) and near objects (object distance of 0.40 m), respectively for a selection of optical lens elements from the series illustrated in Figure 7. (Addition Powers 1.50 D, 2.00 D and 2.50 D). The wearer's distance prescription was assumed to be -3.00 D sphere. The areas of clear vision are defined by a limiting contour of RMS power error equivalent to Add/4 (in diopters) inside a circle of 22 mm radius centred on a point 4 mm below the fitting cross, which will often coincide with the geometric centre of the lens. Zones are coloured pale grey, their size is indicated in mm².

Please replace the second paragraph on page 14, starting on line 18, with the following paragraph:

Figures 12 a-and-b illustrates RMS power error contour plots ray traced for distance objects (object distance of infinity) and near objects (object distance of 0.40 m), respectively for a selection of optical lens elements from the series illustrated in Figure 11. (Addition Powers 1.50 D, 2.00 D and 2.50 D). The wearer's distance prescription was assumed to be +3.00 D sphere. The areas of clear vision are defined by a limiting contour of RMS power error equivalent to Add/4 (in diopters) inside a circle of 22 mm radius centred on a point 4 mm below the fitting cross, which will often coincide with the geometric centre of the lens. Zones are coloured pale grey, their size is indicated in mm².